



SPSCRL

Product Images



Model: SPSCRL

Type: Speaker Strobes; ECS and MNS; AV

L-Series, red, ceiling-mountable, clear lens, speaker strobe marked "FIRE". Selectable strobe settings: 15, 30, 75, 95, 115, 150, and 177 cd.

Product Documentation / Drawings

[Brochure: AV Products \(L-Series...](#)

[Data Sheet: L-Series: Speaker...](#)

[Drawing Files: L-Series: Speak...](#)

[Engineering Spec: L-Series: Sp...](#)

[Product Manual: L-Series: Spe...](#)

Accessories

Required

There are no required accessories for this product.

Optional



BZSPRC

The L-Series BZSPRC is a red bezel for ceiling mount speakers and speaker-strobes. When ordering ind...



SBBCLR

L-Series, red, ceiling surface-mountable back box.



TRC-2

L-Series, red, ceiling-mountable, trim ring that provides additional space in backbox.

Specifications

Candela	Selectable Candela (15, 30, 75, 95, 115, 150, and 177 cd)
Ceiling Mount Dimensions	6.8" dia x 4.5" d
Color	Red
DC Max Op Current	(see Data Sheet for complete current draw information)
Frequency Range	400 to 4000 Hz
FWR Max Op Current	(see Data Sheet for complete current draw information)
Location	Indoor

Marking	FIRE
Maximum Humidity	10 to 93% non-condensing
Mounting	Ceiling
Operating Temperature	32°F to 120°F (0°C to 49°C)
Operating Voltage Range	8 to 17.5 V (12V nominal) or 16 to 33 V (24 nominal)
Operating Voltage Range with MDL	9 to 17.5 V (12V nominal) or 17 to 33 V (24 nominal)
Power	¼, ½, 1, and 2 watts
Series	L-Series
Voltage	25 Volts or 70.7 Volts (nominal)
Wiring Gauge	12-18 AWG

Agency Links





SPSCWL

Product Images



Model: SPSCWL

Type: Speaker Strobes; AV

L-Series, white, ceiling-mountable, clear lens speaker strobe marked "FIRE". Selectable strobe settings: 15, 30, 75, 95, 115, 150, and 177 cd.

Product Documentation / Drawings

[Brochure: AV Products \(L-Series...](#)

[Data Sheet: L-Series: Speaker...](#)

[Drawing Files: L-Series: Speak...](#)

[Engineering Spec: L-Series: Sp...](#)

[Product Manual: L-Series: Spe...](#)

Accessories

Required

There are no required accessories for this product.

Optional



BZSPWC

The L-Series BZSPWC is a white bezel for ceiling mount speakers and speaker-strobes. When ordering i...



LENS-AC2

L-Series, amber lens, used for any indoor ceiling-mountable strobes.



LENS-BC2

L-Series, blue lens, used for any indoor ceiling-mountable strobes.



LENS-GC2

L-Series, green lens, used for any indoor ceiling-mountable strobes.



LENS-RC2

L-Series, red lens, used for any indoor ceiling-mountable strobes.



SBBCWL

L-Series, white, ceiling surface-mountable back box.

Specifications

Candela Selectable Candela (15, 30, 75, 95, 115, 150, and 177 cd)

Ceiling Mount Dimensions: 6.8" dia x 4.5" d

Color	White
DC Max Op Current	(see Data Sheet for complete current draw information)
Frequency Range	400 to 4000 Hz
FWR Max Op Current	(see Data Sheet for complete current draw information)
Location	Indoor
Marking	FIRE
Marking	FIRE
Maximum Humidity	10 to 93% non-condensing
Mounting	Ceiling
Operating Temperature	32°F to 120°F (0°C to 49°C)
Operating Voltage Range	8 to 17.5 V (12V nominal) or 16 to 33 V (24 nominal)
Operating Voltage Range with MDL	9 to 17.5 V (12V nominal) or 17 to 33 V (24 nominal)
Power	¼, ½, 1, and 2 watts
Series	L-Series
Voltage	25 Volts or 70.7 Volts (nominal)
Wiring Gauge	12-18 AWG

Agency Links